CENTRE DE RECHERCHE SUR LES TRANSPORTS
(C.R.T.)
CENTRE FOR RESEARCH ON TRANSPORTATION

UNIVERSITÉ DE MONTRÉAL
ÉCOLE DES HAUTES ÉTUDES COMMERCIALES
ÉCOLE POLYTECHNIQUE

CENTRE DE RECHERCHE SUR LES TRANSPORTS
UNIVERSITÉ DE MONTRÉAL
C.P. 6128, SUCCURSALE A.
MONTRÉAL
CANADA H3C 3J7

TÉLÉPHONE: (514) 343-7575
TÉLEX: (21) 05-561325
EMAIL: crt@crt.umontreal.ca
TÉLÉCOPIEUR (FAX): (514) 343-7121

CRT-634

AN OPTIMAL ALGORITHM FOR WEIGHTED MINIMAX FLOW CENTERS ON TREES

by

Horst A. Eiselt*
and
Michel Gendreau**

* Department of Business Administration, University of New Brunswick, P.O. Box 4400, Fredericton, New Brunswick, CANADA E3B 5A3.

** Centre de recherche sur les transports, Université de Montréal, C.P. 6128, succursale A, Montreal, Quebec, CANADA H3C 3J7.

Centre de recherche sur les transports - Publication #634

May 1989
Revised November 1990

91-01569/

Dépôt légal - 4e trimestre 1990

ABSTRACT

Let a tree be given with supplies assigned to its nodes and weights assigned to its edges. The problem considered here is to locate a facility, so that the flow pattern which results from shipping all supplies to the facility, is such that it minimizes the largest weighted flow on any individual edge. First some properties of such facility locations are derived and then a linear time algorithm for their determination is given.

Key words : facility location; minimax flow problem; location on trees.

- - - - - - -

RÉSUMÉ

Étant donné un arbre, des offres d'un produit aux sommets de cet arbre et des poids associés aux arêtes, nous considérons le problème de la détermination de centres de flot pondéré minimax sur cet arbre, c'est-à-dire de sommets tels que si toutes les quantités du produit présentes dans l'arbre sont envoyées à l'un ou l'autre de ces sommets, le plus grand flot pondéré sur une arête soit minimisé. Nous démontrons d'abord certaines propriétés relatives aux centres de flot pondéré minimax, puis nous décrivons un algorithme en temps linéaire pour leur détermination.

Mots-clés : localisation de ressource; problèmes de flot minimax; localisation de ressource.

INTRODUCTION

In this paper, the following problem is considered. Let a tree be given with supplies at its vertices and nonnegative weights assigned to its edges. The objective is to determine a vertex v* such that if the supplies of all vertices are shipped on their unique paths to v*, then the largest weighted edge flow is as small as possible. A vertex v* with this property is called a **weighted minimax flow center,** or **WMMFC.** The contribution of this paper is the description of a linear time algorithm for the problem. The method described here generalizes earlier results by EISELT and GENDREAU [4] for minimax flow centers with equal weights.

Minimax problems are well-known in the literature. As far as location models are concerned, they are to be distinguished from center (i.e. bottleneck) problems where the largest attribute (i.e. weight) of an edge is sought among all edges which carry any flow; subsequently, this largest attribute is to be minimized. In contrast to that, in our problem the flow is part of the function to be minimized. Minimax flow centers were introduced by EISELT and PEDERZOLI [5]. To our knowledge, the first algorithm for minimax flow problems was provided by MINOUX [7] and a polynomial method was put forward by AHUJA [2]. Some aspects of minimax flows in bipartite graphs were investigated by EISELT [3] and general minimax linear programming problems were solved by AHUJA [1].

THE MODEL AND ITS PROPERTIES

Let $T=(V, E)$ be a tree with set of vertices $V=\{v_1, v_2, \ldots, v_n\}$ and set of edges $E=\{e_1, e_2, \ldots, e_m\}$. The supplies (or similarly, demands) are denoted by $s(v_i) > 0$, $\forall v_i \in V$. The supply of a subtree $\bar{T}$ of T is $s(\bar{T}) = \sum_{v_i \text{ in } \bar{T}} s(v_i)$ and for simplicity, $S=s(T)$. The weights associated with the

edges are $c_k > 0$, $\forall\, e_k \in E$. Furthermore, let $f^*=\{f^*(e_k)\}$ denote the unique flow in T given that the facility to which all supplies are shipped is located at v*. We can then define an (unweighted) minimax flow center (MMFC) as a vertex v* which minimizes

$$z_u^* = \max_{e_\ell \in E} \{ f^*(e_\ell) \}$$

whereas the weighted minimax flow center WMMFC is a vertex v* minimizing

$$z_w^* = \max_{e_\ell \in E} \{ c_\ell \ f^*(e_\ell) \}$$

Furthermore, we will call e_k **a critical edge,** if

$$e_k \in \operatorname*{argmax}_{e_\ell \in E} \{ c_\ell \ f^*(e_\ell) \}$$

and similarly for the unweighted case. It should be pointed out that critical edges in the unweighted problem are always adjacent to the MMFC whereas this is not necessarily the case in the weighted model. In other words, unweighted flows accumulate towards the facility location v* whereas weighted flows do not.

We are now able to state two lemmas concerning the location(s) of WMMFC(s) in a tree.

Lemma 1: Each MMFC of T is also a WMMFC for any edge weight $c_\ell > 0, \forall\, e_\ell \in E$.

Proof: Suppose that v* is an MMFC but not a WMMFC. Let v' be a WMMFC, so that

$$z_w' = \max_{e_\ell \in E} \{ c_\ell \ f'(e_\ell) \} < \max_{e_\ell \in E} \{ c_\ell \ f^*(e_\ell) \} = z_w^* . \qquad (1)$$

Denote the unique path between v^* and v' by $P(v^*, v')$. Note that $f'(e_\ell) = f^*(e_\ell)$, $\forall\, e_\ell \notin P(v^*, v')$. Furthermore, $f'(e_\ell) = S - f^*(e_\ell)$, $\forall\, e_\ell \in P(v^*, v')$. The assumption that v^* is an MMFC implies that $f^*(e_\ell) \leq S/2$, $\forall\, e_\ell \in E$ (see EISELT and GENDREAU [4]). Hence $f'(e_\ell) \geq S/2$, $\forall\, e_\ell \in P(v^*, v')$ and thus

$$f'(e_\ell) \geq f^*(e_\ell), \quad \forall e_\ell \in E. \tag{2}$$

As $c_\ell > 0$, $\forall e_\ell \in E$, condition (2) implies that

$$c_\ell\ f'(e_\ell) \geq c_\ell\ f^*(e_\ell), \forall\ e_\ell \in E$$

and therefore

$$z'_w = \max_{e_\ell \in E} \{c_\ell\ f'(e_\ell)\} \geq \max_{e_\ell \in E} \{c_\ell\ f^*(e_\ell)\} = z^*_w$$

which contradicts condition 1. Consequently, v^* must be a WMMFC. ∎

On the other hand, it can be shown that the converse is not true. Consider the tree in Figure 1 where the numbers next to the vertices represent their respective weights and those next to the edges indicate their weights. Whereas v_3 is the unique MMFC with $z^*_u = 8$, v_2, v_3, v_4 and v_6 are all WMMFCs with edges (v_1, v_3) and (v_5, v_4) carrying a weighted flow of 20 and being thus critical in all cases.



Figure 1

Consequently, if we were only interested in any of the WMMFCs, any algorithm which finds MMFCs could be employed to solve the problem. In the following, we describe properties of the set of all WMMFCs which are then used in the next section in an algorithm.

In the ensuing discussion, let v^* be the location of an MMFC with associated flow pattern f^* and weighted objective value z_w. Furthermore, consider an arbitrary edge $e_k \in E$ whose removal from E subdivides T into two subtrees T_k^1 and T_k^2. Without loss of generality, assume that v^* is in T_k^1. If a WMMFC were to be located at any vertex v'' in T_k^2, then a supply of $s(T_k^1)$ would flow along edge e_k, so that $z_w'' > c_k\ f''(e_k) = c_k\ s(T_k^1)$. In case that $c_k\ s(T_k^1) > z_w$, $z_w'' > z_w$ follows and v'' cannot be a WMMFC. If this occurs, the edge e_k will be called <u>blocking</u>. Note that if the flow pattern f^* is known, the flow $f''(e_k)$ can easily be computed. As $f^*(e_k) = s(T_k^2)$, $f''(e_k) = s(T_k^1) = S - s(T_k^2) = S - f^*(e_k)$.

Consider now some vertex $v'' \neq v^*$ and recall that the flow patterns f'' and f^* differ only on edges on $P(v^*, v'')$; see the proof of lemma 1. Define now a vertex $v' \in V \setminus \{v''\}$ as a predecessor of v'' if $v' \in P(v^*, v'')$ and there is an edge $e' = (v', v'')$. Note that such a vertex always exists (when v'' and v^* are adjacent, $v' = v^*$). Also observe that v' is unique. We can then state

<u>Lemma 2</u>: A vertex $v'' \neq v^*$ is a WMMFC if and only if its predecessor v' is a WMMFC and the edge $e' = (v', v'')$ is not blocking.

Defining V^* as the set of all WMMFCs and E^* the set of non-blocking edges incident to vertices in V^*, lemma 2 implies

<u>Corollary 3</u>: The graph $T^* = (V^*, E^*)$ is a connected subtree of T which contains v^*.

It should be pointed out that in the case where there exists more than one MMFC, the optimal flow pattern f^* identical for all of them. For

any edge e_k on a path connecting any two MMFCs, one has $f^*(e_k) = S/2$. It follows that the MMFCs along with the edges on the paths connecting them form a connected subtree of T^*.

We are now in position to state an algorithm which determines WMMFCs efficiently.

Algorithm: Weighted Minimax Flow Centers in Trees

Step 1: Find an MMFC of T, say v^*, and compute the associated flow pattern f^* and objective value z^*. Compute S.

Step 2: For each vertex v_i, let $E(v_i)$ be the set of edges incident to v_i. Set

$$V^* \leftarrow \{v^*\},$$
$$U \leftarrow \{v^*\}.$$

Step 3: (Processing of unchecked WMMFCs)

While $U \neq \emptyset$ do

[pick some $v' \in U$,
set $U \leftarrow U \setminus \{v'\}$,
perform step 4.

Stop, the set V^* now includes all WMMFCs.

Step 4: (Checking neighbors of v')

While $E(v') \neq \emptyset$ do

[pick some $e_k = (v', v_k)$ in $E(v')$,
set $E(v') \leftarrow E(v') \setminus \{e_k\}$,
set $E(v_k) \leftarrow E(v_k) \setminus \{e_k\}$,
if $c_k(S - f^*(e_k)) < z^*$, then e_k is non-blocking,
set $V^* \leftarrow V^* \cup \{v_k\}$,
set $U \leftarrow U \cup \{v_k\}$.

Two notes are in order with regards to the implementation of this algorithm. First, to allow for the deletion of edges from edge sets $E(v_i)$ in constant time, these should be organized as doubly-linked lists. Secondly, it would be convenient to use a stack for set U.

The complexity of the algorithm can now be evaluated as follows:

- Step 1 can be performed in linear time (i.e. O(n)) by slightly modifying GOLDMAN's [6] algorithm for medians to account for the need to compute f* and z* (see EISELT and GENDREAU [4]).
- Step 2 requires at most O(n) operations, if properly implemented.
- Step 3 is executed at most once for each vertex; not accounting for the operations performed in step 4, each execution requires a constant number of operations.
- The inner loop of step 4 is performed at most (n-1) times: once per edge of T. This loop can also be executed in constant time, yielding an overall complexity of O(n) operations for this step.

The algorithm has thus a worst-case complexity of O(n). Since each of the O(n) parameters of the problem has to be considered at least once by any algorithm, this is also a lower bound on the complexity. The algorithm proposed here is therefore optimal except maybe for a constant factor.

CONCLUSION

In this paper, the problem of finding weighted minimax flow centers in trees has been discussed. First, it was proved that each unweighted minimax flow center is also a WMMFC but not vice versa. Then a linear-time algorithm for the determination of WMMFCs has been described.

Many extensions of the problem studied here can be thought of. One possibility is to consider minimax flow centers in general graphs even though it appears that this problem requires the use of a minimax flow

algorithm which was unnecessary for the problem studied here. This would dramatically increase the computational complexity of the problem. Other possible generalizations include multicommodity minimax flow centers as well as WMMFCs with gains.

ACKNOWLEDGMENTS

This research was supported in part by grants from the Natural Sciences and Engineering Council of Canada under grant numbers OGP0009160 and OGP0038816. This support is gratefully acknowledged.

REFERENCES

1. R.K. AHUJA, "Minimax/Linear Programming Problem", Operations Research Letters 4, 131-134 (1985).

2. R.K. AHUJA, "Algorithms for the Minimax Transportation Problem", Naval Research Logistics Quarterly 33, 725-739 (1986).

3. H.A. EISELT, "Reshipments and Overshipments in Transportation Problems with Minimax Objective", Working paper 87-013, revised version, Faculty of Administration, University of New Brunswick (1988).

4. H.A. EISELT and M. GENDREAU, "On the Determination of Minimax Flow Centers in Trees", publication #738, Centre de recherche sur les transports, Université de Montréal (1990), submitted to Transportation Science.

5. H.A. EISELT and G. PEDERZOLI, "A Location Problem in Graphs", New Zealand Operational Research 12, 49-53 (1984).

6. A.J. GOLDMAN, "Optimal Center Location in Simple Networks", Transportation Science 5, 212-221 (1971).

7. M. MINOUX, "Flots équilibrés et flots avec sécurité", E.D.F. Bulletin de la direction des études et recherches, Série C, 5-16 (1976).